

Joint Filler Dopont

Tile Joint Filler, White and grey



DESCRIPTION

is cementitious compound modified with selected synthetic resins and chemical additives to ensure anti - fungal properties.

FIELDS OF USE

- Durable joint filler for glass, ceramic, mosaic vitreous tiles, synthetic and natural stones.
- Suitable for floor and wall covering tiles.

ADVANTAGES

- Ensures crack free setting up to 5.0 mm. joint width.
- Offers high water tightness and adhesion properties to all types of tiles.
- Can be colored to suit all purposes.

PACKING

Available in weight (20 kg).

STORAGE

12 months in dry and suitable storage conditions.

SAFETY PRECAUTIONS

- Wear gloves, overalls and goggles during handling & application.
- In case of contact, rinse off thoroughly with water.
- wash hands with soap and water after use.

TECHNICAL DATA :(AT 25 °C)

COLOR

white and grey
(other colours upon request) .

RATE OF USE

4-6 m² of 15x15 cm tiles / kg
Depends on dimensions of joints and tiles.

DIRECTIONS FOR USE

- Prepare a paste of Dopont mixed with 25-30% clean water (1 kg. DOPONT powder to 0.25 kg water) by sprinkling the powder on the water and stirring to a pasty consistency free of lumps.
- The paste can be used immediately and within one hour after mixing.
- The paste is applied with a comb, first across and then combed out diagonally to the joint to ensure a complete filling of all joints.
- Immediately after drying begins, smooth down with a damp cloth or sponge and subsequently wipe the surface with dry cloth.
- At higher temperatures, the joint should be kept moist and protected from direct sunlight during setting time.

